



# CS-T12

## Hand-held Bluetooth Printer

Thermal Paper

1D / 2D Barcode

USB + Bluetooth

1500 mAH Rechargeable Battery

Compatible with

 **timecapture**

 **weightcapture**

 **idcapture**

 **farmcapture**

 **secucapture**

Integrated with Capture Manager (MDM)





## Product Parameters

|                          |   |
|--------------------------|---|
| Printing Method          | Thermal Line  |
| Resolution               | 8 dot/mm (203 dpi), 384 dots/line   |
| Printing Speed           | 62mm/s(Max)   |
| Effective Printing Width | 48mm  |
| TPH                      | 50KM  |
| Paper Width              | 57.5±0.5mm  |
| Paper Type               | Thermal Paper   |
| Character Set            | ASCII, GB18030(Chinese), Big5, Codepage, GB12345  |
| Paper Thickness          | 0.06mm~0.08mm   |
| Paper Diameter           | 40mm (Max)  |
| Paper Supply Method      | Drop-in easy loading  |
| Paper Cutting Method     | Manual  |
| Print Font               | Font A: 8 x 16(16 x 16); Font B: 9 x 24; Font C: 12 x 24(24 x 24)                           |
| Barcode                  | 1D: UPC-A, UPC-E, EAN-8, CODE39, CODE93, ITF25, CODE128<br>2D: PDF417, QR CODE, DATA MATRIX |
| Interface                | USB/USB+Bluetooth   |
| SDK                      | Symbian, Windows Mobile, Windows CE, Blackberry, Android, iOS, Windows                      |
| Battery                  | DC7.4V, 1500mAh, Rechargeable<br>Li-ion battery   |
| Charger                  | DC8.4V/1.5A   |
| Operating Temp/Humidity  | 0~50°C/10%~80%  |
| Storage Temp/Humidity    | -20~60°C/10%~90%  |
| Outline Dimension        | 106.5mm*78mm*47mm(L×W×H)  |
| Weight                   | 190g (with battery)   |



[www.capturesolutions.com](http://www.capturesolutions.com)



[info@capturesolutions.com](mailto:info@capturesolutions.com)